

Wrapta Oil-Resistant Dual-Wall Heat Shrink Tubing for Automotive
汽车线束用耐油双壁热缩管

高收缩比, 耐油防水, 汽车线束专用
High Shrink Ratio, Oil & Waterproof, Automotive Harness Solution

汽车线束用耐油双壁热缩管 (Wrapta-A) 专为汽车线束的防水、绝缘和耐油保护设计。其4:1高收缩比, 适用于多种规格的接头和线缆, 简化安装流程。半硬聚烯烃外层耐磨耐油, 内层热熔胶可在收缩时形成牢固密封, 有效防止水分和腐蚀渗透。Wrapta-A能在恶劣环境下, 为汽车线束提供持久、可靠的全方位保护。

Wrapta-A dual-wall oil-resistant heat shrink tubing is designed for automotive wire harness waterproofing, insulation, and oil protection. The 4:1 high shrink ratio fits various connector sizes and cables, simplifying installation. Its semi-rigid polyolefin outer layer resists abrasion and oil, while the adhesive liner creates a strong seal to block moisture and corrosion. Wrapta-A delivers lasting, reliable protection for automotive wire harnesses even in harsh environments.



产品特性与优势 Features and benefits

性能 Property	指标要求 Requirement	测试方法 Test Method	典型值 Typical Data
操作温度范围 Operating Temperature	/	/	-55°C to +130°C
最低收缩温度 Min. Shrink Temperature	/	/	+110°C
完全收缩温度 Full recovery temperature	/	/	+135 °C
抗张强度 Tensile strength	≥10.3MPa	ASTM D 2671	≥14MPa
老化后抗张强度 Tensile strength after aging	初始值的70% 70% of initial value	ASTM D 2671 (158°C, 168 hrs)	≥70%
断裂伸长率 Elongation at break	≥200%	ASTM D 2671	≥200%
老化后断裂伸长率 Elongation at break after aging	≥100%	ASTM D 2671 (158°C, 168 hrs)	≥100%
长度变化率 Longitudinal change	0%~10%	UI223	通过 Pass
热冲击 Heat shock	无裂痕 No Cracking	ASTM D2671 (250°C/4 hrs)	无裂痕 No Cracking
低温柔软性 Low temperature flexibility	无裂痕 No Cracking	ASTM D 2671 (-40°C/4 hrs)	无裂痕 No Cracking
绝缘耐压和击穿 Dielectric voltage withstand	无击穿 No Breakdown	ASTM D 2671 (AC2500V/60S)	无击穿 No Breakdown
体积电阻率 Volume resistivity	≥10 ¹⁴ Ω·cm	ASTM D 876	≥10 ¹⁴ Ω·cm
阻燃性能 Flammability	移火后30秒内自熄 Self extinguishing within 30S after fire source removed	SAE-AMS-DTL -2353/5	通过 Pass
铜腐蚀性 Copper corrosion	通过 Pass	UI224	通过 Pass
吸水性 Water absorption	< 0.5%	ASTM D 570	通过 Pass

- 收缩比4:1
- 半硬阻燃聚烯烃, 耐磨耐腐蚀
- 厚热熔胶层, 优异防水密封保护
- 适用于线束、端子等绝缘防护
- 符合RoHS和REACH认证, 性能可靠

- Shrink ratio 4:1
- Semirigid, flame-retardant polyolefin, abrasion and solvent resistant
- Thick adhesive liner for excellent waterproof sealing
- Ideal for insulation and protection of splices and terminals
- RoHS, and REACH compliant, reliable performance

颜色 COLOR




符合标准 Standards

- SAE-AMS-DTL-2353/5
- RoHS
- REACH

Wrapta

Oil-Resistant Dual-Wall Heat Shrink Tubing for Automotive
汽车线束用耐油双壁热缩管



标准壁厚 Standard wall thickness							
收缩比 Shrink Ratio	编号 Part No.	规格 Size (Φ mm)	收缩前 As supplied (mm)	收缩后 After recovered(mm)			标准长度 Standard length (m/roll)
			最小内径 I.D.min (D)	最大内径 I.D.max (d)	最小壁厚 W.T.min (w)	最小胶厚 Adhesive thickness (l)	
4:1	Wrapta-A-5.72	5.72 (0.225")	5.72	1.27	1.20	0.56	1.22
	Wrapta-A-7.44	7.44 (0.293")	7.44	1.65	1.52	0.76	1.22
	Wrapta-A-10.85	10.85 (0.427")	10.85	2.41	1.91	1.02	1.22
	Wrapta-A-17.78	17.78 (0.700")	17.78	4.45	2.41	1.37	1.22

接受特殊尺寸及颜色定制需求，技术参数如有变更，恕不另行通知。最低订购量(MOQ)可能与包装数量有所不同。
Custom sizes and colors are available upon request. Technical specifications are subject to change without prior notice. Minimum order quantities (MOQ) may differ from standard packaging quantities.

https://www.hzdingyuan.cn/